










Eye & eye flat webbing sling

Technical Parameters

Colour	Colour coded according	Working Load Limit with 1 webbing sling					Working Load Limit with 2 webbing sling			
		Straight lift	Choked lift	ø			Straight 45°	Choked lift up to 45°	Straight lift 45-60°	Choked lift 45-60°
-	-	-	-	0-7°	7-45°	45-60°	< 45°	< 45°	45-60°	45-60°
-	-									
-	-	1	0.8	2	1.4	1	1.4	1.12	1	0.8
WLL 1T	E7DEE010	1,000	800	2,000	1,400	1,000	2,800	1,120	1,000	800
WLL 2T	E7DEE020	2,000	1,600	4,000	2,800	2,000	5,600	2,200	2,000	1,600
WLL 3T	E7DEE030	3,000	2,400	6,000	4,200	3,000	8,400	3,360	3,000	2,400
WLL 4T	E7DEE040	4,000	3,200	8,000	5,600	4,000	11,200	4,480	4,000	3,200
WLL 5T	E7DEE050	5,000	4,000	10,000	7,000	5,000	14,000	5,600	5,000	4,000
WLL 6T	E7DEE060	6,000	4,800	12,000	8,400	6,000	16,800	6,720	6,000	4,800
WLL 8T	E7DEE080	8,000	6,400	16,000	11,200	8,000	22,400	8,960	8,000	6,400
WLL 10T	E7DEE100	10,000	8,000	20,000	14,000	10,000	28,000	11,200	10,000	8,000
WLL 12T	E7DEE120	12,000	9,600	24,000	16,800	12,000	33,600	13,440	12,000	9,600